

SECTION 1: Identification

1.1. Identification

Product form	Mixtures
Product name	Sodium Hydroxide, 50% w/w
CAS-No	1310-73-2
Product code	LC24150
Formula	NaOH
Synonyms	caustic soda 50% W/W / soda lye, 50%, aqueous solution / white caustic, 50%, aqueous solution.

1.2. Recommended use and restrictions on use

Use of the substance/mixture	Industrial use
Recommended use	Laboratory chemicals
Restrictions on use	Not for food, drug or household use

1.3. Supplier

Company name	Aqua Chem Chemical Trading
Address	Al Agamy Al Bahri, Dekhela, Alexandrie, Egypte
Tel	+201 144 455 246
Fax	+201 144 455 246
Email	aquachem@aquachemeg.com

1.4. Emergency telephone number

Emergency number : **+201 144 455 246**

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Hazardous to the aquatic environment - Acute Hazard Category 3	H402	Harmful to aquatic life

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements





GHS-US labeling

Hazard pictograms (GHS-US)	Danger
Signal word (GHS-US)	H314 - Causes severe skin burns and eye damage H402 - Harmful to aquatic life
Hazard statements (GHS-US)	P260 - Do not breathe mist, vapors, spray. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center or doctor/physician. P363 - Wash contaminated clothing before reuse. P405 - Store locked up. P501 - Dispose of contents/container to comply with local, state and federal regulations If inhaled: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards which do not result in classification

No additional information available.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Percentage	GHS-US classification
Sodium Hydroxide	(CAS-No.) 1310-73-2	50	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Water	(CAS-No.) 7732-18-5	50	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general Check the vital functions. Unconscious: maintain adequate airway and respiration.



	Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Do not give activated charcoal. Do not give chemical antidote. Immediately consult a doctor/medical service. Call Poison Information Centre (www.big.be/antigif.htm). Take the container/vomit to the doctor/hospital. Ingestion of large quantities: immediately to hospital. Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of lung edema. Respiratory difficulties.
Symptoms/effects after skin contact	Caustic burns/corrosion of the skin. Slow-healing wounds.
Symptoms/effects after eye contact	Corrosion of the eye tissue. Permanent eye damage. Causes serious eye damage.
Symptoms/effects after ingestion	Vomiting. Diarrhoea. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Bleeding of the gastrointestinal tract. Shock. AFTER ABSORPTION OF LARGE QUANTITIES: Disturbances of consciousness.
Chronic symptoms	ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Skin rash/inflammation. Possible inflammation of the respiratory tract.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	EXTINGUISHING MEDIA FOR SURROUNDING FIRES: Adapt extinguishing media to the
------------------------------	---



Unsuitable extinguishing media environment. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Solid water jet ineffective as extinguishing medium.

5.2. Specific hazards arising from the chemical

Fire hazard	DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Reactions involving a fire hazard: see "Reactivity Hazard".
Explosion hazard	INDIRECT EXPLOSION HAZARD. Reactions with explosion hazards: see "Reactivity Hazard".
Reactivity	Violent exothermic reaction with water (moisture): (increased) risk of fire. On heating: release of corrosive gases/vapours. Absorbs the atmospheric CO ₂ . Violent exothermic reaction with (some) acids. May be corrosive to metals. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire	Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.
Firefighting instructions	Cool tanks/drums with water spray/remove them into safety. Dilute toxic gases with water spray. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.
Protection during firefighting	Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	Gloves. Face-shield. Corrosion-proof suit. Large spills/in enclosed spaces: compressed air apparatus. Large spills/in enclosed spaces: gas-tight suit. See "Material-Handling" to select protective clothing.
Emergency procedures	Mark the danger area. No naked flames. Wash contaminated clothes. Large spills/in confined spaces: consider evacuation. In case of hazardous reactions: keep upwind. In case of reactivity hazard: consider evacuation.

6.1.2. For emergency responders

Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up



For containment	Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Hazardous reaction: measure explosive gas-air mixture. Reaction: dilute combustible gas/vapour with water curtain. Heat exposure: dilute toxic gas/vapour with water spray. Take account of toxic/corrosive precipitation water.
Methods for cleaning up	Take up liquid spill into absorbent material, e.g.: sand, saw dust, kieselguhr. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Small quantities of liquid spill: neutralize with acid solution. Wash away neutralized product with plentiful water. Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle and open the container with care. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Keep away from naked flames/heat. Observe very strict hygiene - avoid contact. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under-local exhaust/ventilation or with respiratory protection.
Hygiene measures	Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Comply with applicable regulations.
Storage conditions	Keep only in the original container in a cool, well ventilated place away from : incompatible materials. Keep container closed when not in use.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	> 15 °C
Heat-ignition	KEEP SUBSTANCE AWAY FROM: heat sources.
Prohibitions on mixed storage	KEEP SUBSTANCE AWAY FROM: combustible materials. strong acids. metals.
Storage area	Store in a dry area. Keep container in a well-ventilated place. Keep locked up. Protect against frost. Provide for a tub to collect spills. Unauthorized persons are not admitted. Meet the legal requirements.
Special rules on packaging	SPECIAL REQUIREMENTS: hermetical. dry. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
Packaging materials	SUITABLE MATERIAL: stainless steel. nickel. polyethylene. polypropylene. glass. stoneware/porcelain. MATERIAL TO AVOID: lead. aluminium. copper. tin. zinc. Bronze.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet : Sodium Hydroxide, 50% w/w



شركة مصر للصناعات الكيماويات
Misr Chemical Industries Co.
شركة تابعة لمساهمة مصرية ش.م.م
إحدى الشركات التابعة للصناعات الكيماوية



Sodium Hydroxide, 50% w/w (1310-73-2)

OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
IDLH	US IDLH (mg/m ³)	10 mg/m ³
NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³

Sodium Hydroxide, 50% w/w (1310-73-2)

ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³ (Sodium hydroxide; USA; Momentary value; TLV - Adopted Value)
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
IDLH	US IDLH (mg/m ³)	10 mg/m ³
NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³

Water (7732-18-5)

Not applicable

8.2. Appropriate engineering controls

Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Protective goggles. Gloves. Protective clothing. Face shield.



Materials for protective clothing:

GIVE EXCELLENT RESISTANCE: nitrile rubber. GIVE GOOD RESISTANCE: No data available. GIVE LESS RESISTANCE: chlorinated

polyethylene. styrene-butadiene rubber. nitrile rubber/PVC. GIVE POOR RESISTANCE: PVA. natural fibres

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or face shield. Face shield

Skin and body protection:

Corrosion-proof clothing

Respiratory protection:

Wear gas mask with filter type B if conc. in air

exposure limit



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid.
Color	Colorless
Odor	Odorless
Odor threshold	No data available
pH	14 (8 %)
pH solution	8 %
Melting point	12 °C
Freezing point	No data available
Boiling point	143 °C
Flash point	Not applicable
Relative evaporation rate (butyl acetate=1)	No data available
Flammability (solid, gas)	Non flammable
Vapor pressure	1.2 hPa (20 °C)
Relative vapor density at 20 °C	No data available
Relative density	1.5
Specific gravity / density	1525 kg/m ³
Molecular mass	40 g/mol
Solubility	Exothermically soluble in water. Soluble in ethanol. Soluble in methanol. Soluble in glycerol.
Log Pow	Water: Complete No data available
Auto-ignition temperature	Not applicable
Decomposition temperature	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	79 mPa.s (20 °C)
Explosion limits	No data available
Explosive properties	Not applicable.
Oxidizing properties	None.

9.2. Other information

Minimum ignition energy	Not applicable
VOC content	Not applicable (inorganic)
Other properties	Clear. Hygroscopic. Slightly volatile. Substance has basic reaction.

10.1. Reactivity



Violent exothermic reaction with water (moisture): (increased) risk of fire. On heating: release of corrosive gases/vapours. Absorbs the atmospheric CO₂. Violent exothermic reaction with (some) acids. May be corrosive to metals. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

10.2. Chemical stability

Stable under normal conditions. Absorbs atmospheric CO₂. Hygroscopic. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Metals.

10.6. Hazardous decomposition products

Sodium oxide. Thermal decomposition generates : Corrosive vapors..

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	Skin and eye contact
Acute toxicity	Not classified

Sodium Hydroxide (1310-73-2)

ATE US (dermal)	1350 mg/kg body weight
-----------------	------------------------

Water (7732-18-5)

LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight
Skin corrosion/irritation	Causes severe skin burns and eye damage. pH: 14 (8 %)
Serious eye damage/irritation	Causes serious eye damage. pH: 14 (8 %)
Respiratory or skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Not classified



Specific target organ toxicity – single exposure	Based on available data, the classification criteria are not met Not classified
Specific target organ toxicity – repeated exposure	Not classified
Aspiration hazard	Not classified
Potential Adverse human health effects and symptoms	Based on available data, the classification criteria are not met. EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of lung edema. Respiratory difficulties.
Symptoms/effects after inhalation	
Symptoms/effects after skin contact	Caustic burns/corrosion of the skin. Slow-healing wounds.
Symptoms/effects after eye contact	Corrosion of the eye tissue. Permanent eye damage. Causes serious eye damage.
Symptoms/effects after ingestion	Vomiting. Diarrhoea. Burns to the gastric/intestinal mucosa. Possible esophageal perforation.
Chronic symptoms	ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Skin rash/inflammation. Possible inflammation of the respiratory tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.
Ecology - air	Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EC) No 842/2006).
Ecology - water	: Ground water pollutant. Maximum concentration in drinking water: 200 mg/l (sodium) (Directive 98/83/EC). Harmful to fishes. Harmful to invertebrates (Daphnia). pH shift.

Sodium Hydroxide (1310-73-2)

LC50 fish 1	45.4 mg/l (LC50; Other; 96 h; Salmo gairdneri; Static system; Fresh water; Experimental value)
-------------	--

12.2. Persistence and degradability

Sodium Hydroxide, 50% w/w (1310-73-2)

Persistence and degradability	Biodegradability: not applicable. No test data on mobility of the components available.
-------------------------------	---

Sodium Hydroxide, 50% w/w (1310-73-2)

Persistence and degradability	Biodegradability: not applicable. No test data on mobility of the substance available.
-------------------------------	--



Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

Water (7732-18-5)

Persistence and degradability Not established.

12.3. Bioaccumulative potential

Sodium Hydroxide, 50% w/w (1310-73-2)

Bioaccumulative potential Does not contain bioaccumulative component(s).

Sodium Hydroxide, 50% w/w (1310-73-2)

Bioaccumulative potential No bioaccumulation data available.

Water (7732-18-5)

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations


13.1. Disposal methods

Waste disposal recommendations	Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle/reuse. Remove for physico-chemical/biological treatment. Do not discharge into drains or the environment
Additional information	LWCA (the Netherlands): KGA category 05. Hazardous waste according to Directive 2008/98/EC
Ecology - waste materials	Avoid release to the environment

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	UN1824 Sodium hydroxide solution, 8, II
UN-No.(DOT)	UN1824
Proper Shipping Name (DOT)	Sodium hydroxide solution
Transport hazard class(es) (DOT)	8 - Class 8 -Corrosive material 49 CFR 173.136
Packing group (DOT)	II - Medium Danger 8 – Corrosive
Hazard labels (DOT)	
DOT Packaging Non Bulk (49 CFR 173.xxx)	202
DOT Packaging Bulk (49 CFR 173.xxx)	242 B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.
DOT Special Provisions (49 CFR 172.102)	T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be



calculated using the formula: (image)

Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively

DOT Packaging Exceptions (49 CFR 173.xxx)

154

DOT Quantity Limitations Passenger aircraft/rail

1 L

(49 CFR 173.27)

30 L

A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

52 - Stow "separated from" acids

DOT Vessel Stowage Location

No supplementary information available.

SECTION 15: Regulatory information

15.1. US Federal regulations

Sodium Hydroxide, 50% w/w (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313.

RQ (Reportable quantity, section 304 of EPA's List of Lists)

1000 lb

SARA Section 311/312 Hazard Health hazard - Skin corrosion or Irritation

Classes Health hazard - Serious eye damage or eye irritation

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Sodium Hydroxide, 50% w/w (1310-73-2)

RQ (Reportable quantity, section 304 of EPA's List of Lists)

1000 lb

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard

15.2. International regulations

CANADA

Sodium Hydroxide, 50% w/w (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available



National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

SECTION 16: Other information

Revision date	
Other information	

Full text of H-phrases: see section 16:

H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life
NFPA health hazard	3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	0 - Materials that will not burn under typical dire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA reactivity	1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.
Hazard Rating Health	3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	0 Minimal Hazard - Materials that will not burn
Physical	1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.
Personal protection	H H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

